

STYLUS®
ALKALINE BATTERY-POWERED PEN LIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Hardware/Tool, Sporting Goods, Fire & Rescue, Industrial Safety, Occupational Safety, Automotive, Gift, Consumer

DESCRIPTION: Ultra-slim pen light with a high intensity LED.
 Perfect for tactical use and covert operation while preserving night vision.

CASE MATERIAL: Machined aluminum case with non-slip knurled grip.
 Available in black, gold, silver, red, blue or flag anodized finish.

DIMENSIONS: Length: 6.21 in. (15.17 cm) Diameter: 0.375 in. (0.95 cm)

WEIGHT: 1.1 oz (31 grams) with batteries (included with purchase).

LIGHT SOURCE: High intensity 5mm LED, impervious to shock with a 100,000 hour lifetime.
 Available in White, Blue (470nm), Red (624nm), Green (527nm), UV (365nm) or IR (880nm).

LIGHT OUTPUT: White: 140 candela peak beam intensity, 24m beam distance, 11 lumens measured system output.
 Blue: 110 candela peak beam intensity, 21m beam distance and 2 lumens measured system output.
 Red: 53 candela peak beam intensity, 15m beam distance and 2 lumens measured system output.
 Green: 59 candela peak beam intensity, 15m beam distance and 7 lumens measured system output.
 UV: 3.8 mW measured system output.
 IR: 12 mW/sr measured system output.
 See model for specific LED selection.



ON/OFF: Features momentary blink or constant “on” operation.


RUN TIME: 24 continuous hours to the 10% lumen output level.

BATTERY: 3 “AAAA” size alkaline batteries.

FEATURES: High intensity LED.
 Individually serialized for positive identification.
 IPX4 Rated for water resistant operation.
 2 meter impact resistance tested
 Removable pocket clip.
 Glare guard protector included in package.

APPROVALS*: (specific models)

 Class I, Division 1, Groups A, B, C, D, T3C Exia


 II 2G Ex ia op is IIB T2 Gb - FTZU 11 ATEX 0057X
 Ex ia op is IIB T2 Gb - IECEx FTZU 15.0026X

 Most models meet applicable European Community Directives.

WARRANTY: Streamlight’s Limited Lifetime Warranty

OPTIONAL ACCESSORIES: Glare Guard, Holster, Lanyard

PERFORMANCE CURVE



*See product for specific ratings.
 All performance claims to ANSI/PLATO FL1-2016 Standard
 Issued: 10/01/2004
 Revised: 02/13/2018 Rev: 7